

Always. Reliable. Tight.

Standard press seal

sealing width 40 mm

HSD150 1x110 b40 A2/EPDM55

Article no.: 1650015110, GTIN: 4052487121941



- **optical and tangible installation security due to integrated control opening**

For sealing new pipes to be installed or pipes that have already been laid in core drills or wall sleeves. Available for delivery for all standard pipe sizes.



Picture may differ from selected product

FACTS

Application range:

- DIN 18533 W1.1-E, DIN 18533 W1.2-E, DIN 18533 W2.1-E, DIN 18533 W2.2-E
- Waterproof concrete stress class 1, Waterproof concrete stress class 2

Advantages:

- Can be split on site up to Ø 200 mm for retrofit installation
- Split as standard at and above Ø 250 mm
- All manner of material combinations are available for tailor-made applications
- Available from stock

Dimensions:

- Sealing width: 40 mm

Properties:

- U-profile: maximum stability for press segments

Material:

- Press plates, screws and nuts: rust-free stainless steel V2A (AISI 304L) or V4A (AISI 316L)
- Rubber: EDPM, NBR or with KTW approval

Tightness:

- Gastight and watertight

FEATURES

Wall sleeve/core drilled hole ID (mm):	150
Suitable for medium pipe OD from (mm):	110
Suitable for medium pipe OD to (mm):	113

PICTURES

