

Datasheet Radon Scout Plus



Radon Scout Plus


[more information](#)

Radon Scout PLUS

Technical Data



- Measurement Range 0 ... 10 MBq/m³
- Sensitivity 1.8 cpm @ 1000 Bq/m³ (independent on the humidity)
 - 200 Bq/m³ with 20% statistical error (1 σ) at 1 hour interval
 - 1000 Bq/m³ with an statistical error (1 σ) < 10 % at 1 hour interval
 - 100 Bq/m³ with 17% statistical error (1 σ) at 3 h interval
- Response Time 120 Minutes to 95% of the final value
- Internal sensors for
 - Relative humidity (0 ... 100%)
 - Temperature (-20 ... 40°C)
 - **Barometric pressure (800 ... 1200 mbar)**
 - Tilt
- Integration interval 1 ... 255 Minutes adjustable by software
- Non volatile storage of the last 16383 data records, RS232 and USB interface
- Internal real time clock
- Power supply 2 x D-size cell (NiCd, NiMH or Alkaline) and mains power
- Battery operation > 90 days
- Control by a single switch, measurement/stand-by (lock-function)
- **3 x 16 characters display with back-light (US/SI units selectable by software)**
- Size 175 x 135 x 55 mm, weight 800 g (incl. Battery)
- Radon Vision Software included
 - Set-up, data download (also via ZigBee or modem – analogue line, ISDN, GSM)
 - Interactive graphical display (zoom, pan, fit data-cursor, marker for tilt and start of a new measurement, error bars, smoothing)
 - Selective ASCII export (EXCEL format)
 - Selective graphical protocol print (space for individual header, user comments)
 - Calculation of average concentration and exposure
 - Automatic created file names and path structure
 - Switch over between US and SI-units (Bq/m³/pCi/L)



```
0Bq/m³ ± 0%  
14:51 1003mbar  
24.0°C 57% 1.37V
```



```
Avg: 0Bq/m³  
>>06/06/28 14:38  
2/5min #2
```